

Lifetime, Temperature Range

Radial 6V - 100V	Standard & Miniature 1.000 - 4.000h / 85°C	Semi-Professional 1.000 - 3.000h / 105°C	Professional / Long Life 3.000 - 12.000h / 105°C	Extra Long Life High Temperature 1.500 - 4.000h / 125°C
Large Size	CD 110 PT Standard Page: 18	CD 263 BK Standard Page: 26	CD 286 GK CD 289 PB Low ESR	CD 265 TW 125°C
	CD 11C CX 7mm Height	CD 267 PM Large Size	CD 287 GC Low ESR Page: 37	CD 281 LL Longest Life Page: 31
	CD 50S WL 5mm Height	CD 70H QG 7mm Height	CD 28L QL Miniaturized Page: 40	CD 284 XY Lowest Impedance Page: 34
Small Size		CD 50H WH 5mm Height	CD 283 DZ Extra Low Imp.	
Specialities & Polymer	CD 11A PA (Audio, Low Noise) CD 117 DL (Low Leakage) CD 71 NP (Bipolar) CD 71C NC (Bipolar 7mm) CD 50BP WB (Bipolar 5mm)	CD 117H DH (Low Leakage) CD 71H NH (Bipolar)	HCP Polymer-Low ESR Page: 80 HPM Polymer-Small Size Page: 82	

Lifetime, Temperature Range

Radial 160V - 450V	Standard & Miniature 2.000 - 4.000h / 85°C	Semi-Professional 1.500 - 4.000h / 105°C	Professional / Long Life 6.000 - 14.000h / 105°C	Extra Long Life High Temperature 2.500h / 125°C
Large Size	CD 110 PT Standard Page: 18	CD 267 PM Large Size	CD 266 FK Longer Life	
		CD 263 BK Standard Page: 26	CD 261 LK High Current Page: 20	CD 262 QM Longest Life Page: 24
		CD 11H PD High Current	CD 261X QX Highest Currents Page: 22	CD 11G GW High Voltage 125°C
Small Size		CD 264 KH Low Impedance		

Lifetime, Temperature Range

SMD	Standard 1.000 - 3.000h / 85°C	Professional 2.000 - 3.000h / 105°C
Large Size	CD VS BS Standard Page: 12	CD VH VH Standard Page: 14
Small Size		CD VZ VZ Low ESR Page: 16
Specialities & Polymer	CD VB VB Bipolar	HVC Polymer-Low ESR Page: 79

Lifetime, Temperature Range

Snap-In	Standard 3.000 - 4.000h / 85°C	Professional 6.000 - 7.000h / 85°C	Standard 3.000 - 4.000h / 105°C	Professional 5.000 - 9.000h / 105°C
Large Size	CD 293 BZ Standard Page: 43	CD 29L QL Larger Size Page: 64	CD 294 BW Standard Page: 46	
		CD 295 BC Longer Life Page: 49		CD 296 KC 5.000h Page: 52
		CD 29D HR Highest Currents Page: 60		CD 297 BB 7.000h Page: 55
Small Size	CD 291 PE (Lug) CD 292 PF (Soldering)		CD 29S PJ (Mini)	CD 29H QH Highest Currents Page: 62
				CD 299 PG 9.000h Page: 58

Lifetime, Temperature Range

Screw	Standard 4.000h / 85°C	Professional 10.000h / 85°C	High End 20.000h / 85°C	Standard 4.000h / 105°C	Professional 9.000h / 105°C
Large Size	CD 135 BP Standard Page: 66	CD 138 PC High Current Page: 73	CD 13L PL Long Life	CD 136 PK Standard Page: 69	CD 139 BL Longest Life Page: 75
Small Size	CD 135X BX Miniaturized	CD 137 PX Highest Voltage Page: 71			